

## **Product Specification Sheet**

12464 — .335 Kerf PS

This product is being offered as a potential replacement to Rochester's Urethane C03 / U03 QEZD-375

**Product Description:** .335" kerf mount foam profile designed to fit a kerf slot with a width of .078" and minimum depth of .250".

**Features:** Seamless compression seals are nearly 100% closed cell to prevent water from penetrating foam cell structure. Extruded skin provides a unique UV resistant barrier with design features that enhance the weather strip's sealing performance.

This product features our Pro-Slip II HDPE coating which provides excellent durability and co-efficient of friction properties making it a great choice for sliding applications

## Compression:

Recommended = 25% Minimum = 10% Maximum = 50%

## .400 .335 .275

## Achieves AAMA 702 Class "A" Extra High Performance Certification

Profile	12464 —.335 KERF PS
Colors	Brown, Black, Bright White and Tan
Part Numbers and Descriptions	12464111691000 .335 KERF PS BRN CONT 12464112091000 .335 KERF PS BLK CONT 12464112191000 .335 KERF PS BRT WHT CONT 12464112591000 .335 KERF PS TAN CONT
Packaging and Box Quantities	1,000' per reel—2 reels per box (2,000' per box) Box dimensions 26 1/4" X 18 1/2" X 26 1/4" (H X W X L)
Pallet Quantities and Dimensions	8 boxes per pallet; 16,000' per pallet Pallet dimensions 58" X 40" X 54" (H X W X L)
Minimum Order Quantities	12,000' minimum total order quantity with a 6,000' minimum quantity per color
Samples	25' samples available for customer testing Colors swatches available upon request

